MAEK.

Prepared For:

Liberty Roofing Center 1 860 Charles St. Gloucester, NJ 08030

Presented By:

Cambria Truck Center 116 Talmadge Rd Edison, NJ 08817 800-899-5226 Page 1

Jul 21, 2014 2015 GU533 Ref#: AIMQ026515A

Description

ORDER/CUSTOMER/VEHICLE INFORMATION

INITIAL REGISTRATION LOCATION, UNITED STATES, NEW JERSEY

LANGUAGE, ENGLISH

IDLE EMISSION CERTIFICATION, IDLE EMISSION CERTIFICATION - CARB 08

TYPE OF SERVICE, COMMERCIAL

VEHICLE APPLICATION CLASS, NORMAL HIGHWAY - Unlimited operation on concrete or asphalt with a maximum 3% grade;

limited operation on maintained gravel/packed dirt with a maximum 3% grade; and limited operation on concrete or asphalt with a maximum 8% grade. No operation on unmaintained surfaces. (2 AXLES) 50,000 lbs (22,680 kg) MAX GVW. (3 AXLES) 63,000 lbs (28,576 kg) MAX GVW.

CARRIER APPLICATION, NOT AVAILABLE

VEHICLE TYPE, STRAIGHT TRUCK WITHOUT TRAILER

VEHICLE USE AND BODY/TRAILER TYPE, PLATFORM Inner City

BRAKE - STOPPING DISTANCE, BRAKE REGULATION, STOPPING DISTANCE 94M (310FT)

FILE STATUS, SOLD ORDER

PRICE BOOK LEVEL, 2015A PRICE BOOK LEVEL

PRODUCT TYPE, PRODUCT TYPE - CML64R TRUCK

PRODUCT CLASS, PRODUCT CLASS 28

BACK OFFICE PROCESS, BACK OFFICE PROCESS

BVS/FRT AXLE POS/SALES PACKAGES

CHASSIS (BASE MODEL), GU503 6-WHEEL TRUCK

CHASSIS PACKAGING SOLUTIONS, PACKAGE 2 INCLUDES: Cummins Switchback DPF, RH Battery Box, Air Under B

Box - remaining on rail REQUIRES: LH Fuel Sleeved Single Fuel Tank, Omit RH Tank

ENGINE/TRANSMISSION/CLUTCH

ENGINE, CUMMINS ISL-D 345 HP @1600-1900 RPM (PEAK) 1150 LB. FT. MAX. TORQUE @ 1400 RPM

TRANSMISSION, 10 SPEED MANUAL (OVERDRIVE), FULLER FRO-11210C (12.69/0.74)

CLUTCH, SELF ADJUSTING, 1335601 EATON ADVANTAGE SOLO, 7-SPRING, 2-PLATE, 15.5" CERAMIC CLUTCH, 4

PADDLES, SELF ADJ

PLUS DPF VERSION 3

EXHAUST/EMISSIONS

DPF, DPF, HORIZ RH SIDE UNDER CAB & BEHIND STEP CUMMINS SWITCHBACK

EXHAUST AFTER-TREATMENT SYSTEM, EXHAUST AFTER-TREATMENT SYSTEM SELECTIVE CATALYST REDUCTION

DPF SMART SWITCH, NO INHIBIT DPF REGENERATION SWITCH

EXHAUST, SINGLE (R/S) VERT EXHAUST CAB MOUNTED, LOWER VENTURI DIFFUSER, TURNED END

SINGLE, BRIGHT FINISH STACK ONLY

FURNISH STEEL PAINTED HEAT SHIELD FOR FRAME MTD DPF (CUMMINS)

ENGINE EQUIPMENT

AIR COMPRESSOR, MERITOR/WABCO 318 18.7 CFM

ALTERNATOR, DELCO 12V 130A (24SI) BRUSH-TYPE

BATTERIES, (3) MACK 12V 760 CCA THREADED STUD TYPE

BUG SCREEN, BLACK ALUMINUM MOUNTED BEHIND GRILLE

TEXACO EXTENDED LIFE COOLANT W/NITRITES (50/50 MIX) TO -34 DEG

ENGINE BRAKE, JACOBS C BRAKE, 2 POSITION

ENGINE BLOCK HEATER, 120V 1000 WATT ENGINE BLOCK HEATER

FAN DRIVE, HORTON DMA2S-TWO SPEED, ON/OFF CLUTCH W/LIGHTWEIGHT PLASTIC FAN

Description

FUEL-WATER SEPARATOR, DAVCO 382, NON-HEATED W/VENDOR PRIM & MACK SEC FUEL FILTER

HOSES - RADIATOR/HEATER, SILICONE

OIL PAN HEATER, W/O OIL PAN HEATER

ELECTRIC PREHEATER

STARTER, 12 VOLT DELCO 39MT-MXT

TETHER DEVICE, FURNISH CAP RETAINER FOR OIL FILL & RADIATOR OVERFLOW TANK, BATTERY BOX, AND TOOL BOX (WHEN FURNISHED)

Ref#: AIMQ026515A

TRANSMISSION EQUIPMENT/DRIVELINES

CLUTCH ASSIST (AIR), MECHANICAL CABLE

CLUTCH PEDAL, OPEN GRATED TYPE

CLUTCH RELEASE HOSE, CLUTCH RELEASE LUBE HOSE

TRANSMISSION BELL HOUSING, IRON

W/O TRANSMISSION DUSTPROOFING

SYNTHETIC LUBRICANT - TRANSMISSION, 50W (SYNTHETIC LUBRICANT)

WITHOUT DRIVESHAFT GUARD FOR CENTER BEARING

DRIVELINE - MAIN, MERITOR 176 MXL "XTENDED LUBE"

DRIVELINE - INTERAXLE, MERITOR 17 MXL "XTENDED LUBE"

CAB (A thru G)

MACK (BERGSTROM) INTEGRAL W/HEATER COMBINATION HEATER/DEFROSTER AND CONDITIONER

AIR RESTRICTION MONITOR (INTAKE), W/O AIR RESTRICTION MONITOR

CAB, LH-DRIVE CA68 CONV CAB

AUX. INCAB PNEUMATIC LINE CLEANOUT

CAB MOUNTING, AIR SUSPENSION

CERTIFIED WEIGHT

TWO (2) EXTRA DASH MOUNTED ILLUMINATED TOGGLE SWITCHES

PARK BRAKE AND ENGINE RUNNING ACTIVATED

(4) DOME LAMPS - DOOR AND SWITCH ACTIVATED

DOOR INTERIOR TRIM PANELS, PADDED VINYL WITH ARM REST PADS

FENDER EXTENSIONS, FENDER EXTENSIONS

5LB (ABC RATED/AMEREX) MOUNTED BETWEEN LH SEAT BASE AND DOOR WITH VALVE AIMED REARWARD

FLOOR COVERING, POLYURETHANE FLOOR MAT W/POLYURETHANE INSERTS BOTH DRIVER & PASSENGER SIDES

GAUGE CLUSTER, EXHAUST PYROMETER AND TRANSMISSION OIL TEMPERATURE GAUGES

GAUGES, ENGLISH/METRIC DISPLAY

WITHOUT REAR AXLE OIL TEMPERATURE GAUGE

W/O INSIDE/OUTSIDE TEMP GAUGE OPTION

GEAR SHIFT, W/O OPTIONAL GEAR SHIFTER

GLASS - CAB WINDOW, SAFETY TINTED WINDSHIELD, SIDE AND REAR WINDOWS

DIAGONAL GRAB HANDLE ON INSIDE DRIVER'S DOOR

GRILLE - HOOD AIR INTAKE, GRILLE PAINTED GRAY

GRILLE, BLACK FINISH BARS W/PLATINUM (NICKEL BRUSHED) SURROUND RADIATOR MOUNTED

CAB (H thru R)

HEADLINER, VINYL COVERED FOAM PADDED HEADLINER

PAINTED HOOD LATCHES

HORN - AIR, TWIN-U/CAB TRUMPET

HORN - ELECTRIC, DUAL TONE (TWO HORNS)

IDENTIFICATION/CLEARANCE LIGHTS, (5) TRUCKLITE LED CHROME BULLET TYPE LAMPS

Description

IN-DASH STORAGE, LARGE STORAGE POCKET

INSTRUMENT CLUSTER DISPLAY, CO-PILOT DRIVER DISPLAY, ENHANCED 4.5" DIAGONAL LCD DISPLAY W/4-BUTTON STALK CONTROL

Ref#: AIMQ026515A

INTERIOR TRIM (PUREBRED - SLATE GRAY) Vinyl headliner & seat covering, 2 netted storage compartments and center CB radio mounting provisions in overhead console, rear panel with storage pouch, polyurethane floor mat, 2 cup holders, slate gray instrument panel with black gauge bezel, Sandstone door panels & trim, RH door peep window, padded interior sun visor - driver side only, 2 spoke slate grey urethane cushion grip steering wheel with Bulldog horn button, hand crank lh/rh windows, 2 general overhead lights, 1 driver overhead light & 1 map non-glare overhead light, 2 12V power sources, seat belts, lap and shoulder w/cab mtd shoulderbelt, 2 coat hangers, 2 trash bag hooks, RH storage compartment, RH Door Peep Window

CHASSIS KEYED AT RANDOM - 2 KEYS

MIRRORS - EXTERIOR, HTD & ILLUMINATED BULLDOGS - BRIGHT FINISH

MIRRORS - CONVEX TYPE, BRIGHT FINISH, LH & RH 8.0" DIA HEATED; MOUNTED BELOW LOWER ARM OF WEST COAST MIRROR

MIRRORS - PROXIMITY, RECT CONVEX ABOVE RH DOOR WINDOW

OVERHEAD CONSOLE, (2) STORAGE COMPARTMENTS AND NET RETAINERS W/CENTER MOUNTING FOR CB PROVISIONS

AM/FM PREMIUM STEREO, CD-PLAYER, MP3, WEATHERBAND, HANDSFREE INTERFACE, BLUETOOTH

RADIO ANTENNA, CAB MOUNTED BEHIND LH DOOR

RADIO ANTENNA - CB, SINGLE DRIVER SIDE

CB RADIO MOUNTING REINFORCEMENT IN HEADER CONSOLE

RADIO SHUTOFF, AUTO SHUTOFF FOR RADIO ENTERTAINMENT SYSTEM (WHEN IN REVERSE)

CAB (S thru Z)

SEAT - DRIVER, AIR-NATIONAL 2000 (HI-BACK) SINGLE CHAMBER AIR LUMBAR, 2 POSITION FRONT CUSHION ADJ.

SEAT - RIDER, EXTENDED, NON-SUSPENSION WITH SEAT BELTS (2)

SEAT ARM RESTS, INBOARD MOUNTED ARM REST, DRIVER'S SEAT ONLY

SEAT COVERING, ALL VINYL DRIVER & RIDER SEATS

LAP AND SHOULDER FOR DRIVER AND OUTBOARD RIDER AND LAP BELT FOR INBOARD RIDER

W/O ROOF VENT VENTILATION

STEERING COLUMN, ADJUSTABLE TILT TELESCOPE

STEERING WHEEL, TWO SPOKE URETHANE GRIP PAINTED SPOKES & BULLDOG HORN CAP

STORAGE POUCH REAR

SUN VISOR, EXTERIOR, FIBERGLASS (CAB COLOR)

SUN VISOR - INTERIOR, BOTH SIDES (PADDED VINYL)

TURN SIGNAL SWITCH, SELF CANCELLING TURN SIGNALS

WINDOW CONTROLS, POWER ELECTRIC RH WINDOW & POWER ELECTRIC RH DOOR LOCK

WINDSHIELD, 2-PIECE WINDSHIELD

WINDSHIELD WASHER RESERVOIR, WINDSHIELD WASHER RESERVOIR INSTALLED BOC

WINDSHIELD WIPERS, 2 SPEED ELECTRIC MOTOR W/INTERMITTENT FEATURE

COMMUNICATIONS SYSTEMS

W/O GUARDDOG CONNECT OR DIAGNOSTIC SERVICES

FRAME EQUIPMENT/FUEL TANKS

BUMPER - FRONT, FLUSH-SWEPT BACK CHANNEL PAINTED STEEL 116.5"/2959 mm BBC

CROSSMEMBERS, BOC AND INTERMEDIATE(S) STEEL HD BACK-TO-BACK CHANNEL

CROSSMEMBER (BEHIND REAR AXLE), STEEL SINGLE CHANNEL (1) W/AF of 70" to 129".

FRONT FRAME EXTENSION, W/O FRONT FRAME EXTENSION

TOWING DEVICE - FRONT, (2) CLEVIS

-

Description

FUEL TANK - LH, 111 GALLON (420 L) STEEL, SLEEVED D-SHAPED

FUEL TANK - RH, OMIT RH STANDARD

STANDARD FINISH STEPS AND BRIGHT FINISH STRAPS - FUEL TANK

6.6 GALLON (25 L) 22" DIAMETER TANK LEFT SIDE FRAME MTD

WITHOUT DEF TANK COVER

RELOCATE FUEL TANK, W/O RELOCATED FUEL TANK(S)

FRONT AXLE/EQUIPMENT/TIRES

FRONT AXLE, 20000# (9072kg) MACK FXL20 WIDE PIVOT CENTER STRAIGHT SPINDLE/UNITIZED BEARINGS

TIRES BRAND/TYPE - FRONT, BRIDGESTONE - TUBELESS RADIAL PLY, (2) 315/80R22.5 20 L M860A (ALL POS)

WHEELS - FRONT, STEEL DISC (10-HOLE)

(2) 22.5x9.0 (228 mm) HAYES LEMMERZ 10-HOLE HUB PILOTED (11 1/4"/286mm BC)(FIVE HAND HOLE)(6.42" INSET)

Ref#: AIMQ026515A

WHEELS - POLISHED (FRONT), W/O FRONT DISC WHEEL BRIGHT FINISH

BRAKES - FRONT, MERITOR "S" CAM TYPE 16.5" x 6" Q+

BRAKE DRUMS - FRONT, CAST OUTBOARD MOUNTED

DUST SHIELDS - FRONT BRAKE, OMIT

HUBS - FRONT, FERROUS

FAG SCHAEFFLER, FRONT GREASE SEAL

SHOCK ABSORBERS, FRONT

SLACK ADJUSTERS - FRONT, MERITOR - AUTOMATIC

SPRINGS - FRONT, MACK MULTILEAF 20000# (9072kg) GROUND LOAD RATING

STEERING, M100P + M90 SHEPPARD POWER

REAR AXLE/EQUIPMENT/TIRES/RATIOS

REAR AXLE/SUSPENSION, 40000# (18144kg) MERITOR MT-40-14X4D HYPOID (LOW ENTRY), MT-40-14X4D MACK AL-402

AIR 40000# CAPACITY

W/O WIDE TRACK AXLE OPTION

TIRES BRAND/TYPE - REAR, BRIDGESTONE - TUBELESS RADIAL PLY, (8) 11R22.5 14 G M726EL (TRACTION)

CARRIER/RATIO - REAR AXLE, MALLEABLE HOUSING, 4.88 RATIO

WHEELS - REAR, STEEL DISC (10 HOLE)

(8) 22.5x8.25 (210 mm) HAYES LEMMERZ 10-HOLE HUB PILOTED (11 1/4"/286 mm BC)(FIVE HAND HOLE)

BRAKES - REAR, MERITOR "S" CAM 16.5"x7" Q+

BRAKE DRUMS - REAR, CAST OUTBOARD MOUNTED

DUST SHIELDS - REAR BRAKE, OMIT

HUBS - REAR, FERROUS

OIL SEALS, CHICAGO RAWHIDE (SCOTSEAL)

POWER DIVIDER LOCKOUT W/WARNING LIGHT AND BUZZER (INCLUDES IN CAB MANUAL AIR VALVE)

SHOCK ABSORBERS - (4), MOUNTED ON FORWARD AND REAR AXLES EACH SIDE

SLACK ADJUSTERS - REAR, MERITOR - AUTOMATIC

SUSPENSION - AXLE SPACING, 52" AXLE SPACING (BOGIE WHEELBASE)

SUSPENSION - HEIGHT CONTROL KIT, MACK CONTROL KIT W/WARNING LIGHT AND BUZZER

SPRING BRAKE CHAMBERS - VENDOR, MGM TR-T (TAMPER RESISTANT BRAKE CHAMBERS) RECLOCK INLET PORTS

FOR OPTIMUM GROUND CLEARANCE

REAR SPRING BRAKE CHAMBERS 30/30 TYPE

SYNTHETIC LUBRICANT - REAR AXLE, 75W - 90 (SYNTHETIC LUBRICANT) - SYNTHETIC

TRANSVERSE TORQUE RODS (BOTH AXLES)

DRIVER CONTROLLED INTER WHEEL DIFFERENTIAL LOCK FRT RR AXLE, MANUAL AIR VALVE W/WARNING LIGHT.

W/O PROTECTIVE NYLON SPACER BETWEEN DISCS WHEEL TO DRUM

Description

FRAME/WHEELBASE/PLATFORM

WHEELBASE, 270 CA, 205

PLATFORM, 295 AF, 112

FRAME RAILS, 11.811" x 3.54" x .44" (300 x 90 x 11.1mm) STEEL Section Modulus: 23.5 cu in/RBM 2,820,000 in lbs per rail

Ref#: AIMQ026515A

FRAME REINFORCEMENT - INSIDE, W/O 5MM INSIDE CHANNEL REIFORCEMENT

AIR/BRAKE

AIR DRYER, MERITOR/WABCO HEATED AIR DRYER, 1200 W/COALESCING OIL FILTER

W/O RELOCATED AIR TANKS

ANTI-LOCK BRAKE SYSTEM, BENDIX WITHOUT TRACTION CONTROL

AIR CONTROL VALVES - VENDOR, BENDIX SWITCHES AND VALVES WHERE POSSIBLE

BRAKE CONTROL VALVE SYSTEM, SINGLE VALVE SYSTEM

DRAIN VALVES, MANUAL (PETCOCK) DRAIN VALVES ON ALL TANKS

W/O HAND CONTROL VALVE

W/O TRAILER ACCESS PACKAGE

TRAILER CONNECTIONS

TRAILER AIR CONNECTIONS, OMIT TRAILER AIR BRAKE CONNECTIONS

TRAILER ELECTRICAL RECEPTACLE, SINGLE 7 PINS STD SAE TYPE, END OF FRAME

OMIT TRAILER CONNECTORS HOLDER

ELECTRICAL

BACK-UP ALARM, W/INTERMITTENT FEATURE (AMBIENT NOISE SENSITIVE) 87-112 db

BATTERY BOX COVERS, MOLDED PLASTIC

BATTERY BOX - MOUNTING, RIGHT HAND BEHIND SCR

W/O OPTIONAL DASH MTD. LIGHT

CHASSIS & POWER HARNESS WITH STANDARD CASING

"BODY LINK" III W/CAB PASS-THRU

REAR LIGHTING, FURNISH REAR LIGHTING

WORK LIGHTS, RH/LH LED WORK LIGHT (STEPS & GROUND) ON BOTH SIDES TRUCK

PAINT

PAINT - CAB EXTERIOR, SINGLE COLOR, MACK WHITE (HIGH GLOSS)

PAINT - CAB, URETHANE BASE COAT W/O CLEAR COAT

PAINT - CHASSIS RUNNING GEAR, MACK BLACK (URETHANE)

PAINT - FUEL TANK, SAME AS CHASSIS RUNNING GEAR

PAINT - FRONT SPOKE WHEELS, WITHOUT OPTIONAL SPOKE WHEEL PAINT

WITHOUT OPTIONAL SPOKE WHEEL PAINT

PRE-FINISHED POWDER COAT WHITE

PRE-FINISHED POWDER COAT WHITE

PAINT PROCESS CODES

W/O PAINT FOR BUMPER (5ZB-Z1X)

CHASSIS RUNNING GEAR - STD COLOR (MACK BLACK) (6AB-Z1X)

SAME COLOR AS CHASSIS RUNNING GEAR (7HB-A1X)

W/O CUSTOM PAINT FOR HUB&DRUM/SPOKES (5YB-Z1X)

W/O CUSTOM PAINTED FRONT/REAR RIM/WHEEL (6BB-Z1X)

PTO/SPECIALTY/ADDITIONAL EQUIPMENT

PTO - REAR ENGINE (REPTO), WITHOUT REAR ENGINE POWER TAKE OFF

W/O SPECIAL DECALS

V-MAC IV PROGRAMMABLE PARAMETERS

Ref#: AIMQ026515A

Description

CUSTOMER VEHICLE LIMITING SPEED (MPH) 65 mph

PEDAL ROAD SPEED LIMITER (MPH) 65 mph

LGVLS FEATURE ACTIVATION Omit

LOWER GEAR VEHICLE LIMITING SPEED (MPH) 00 mph

SOFT RSL Omit

PDLO ENGAGED VEHICLE LIMITING SPEED 00 rpm

CRUISE CONTROL SETTINGS W/O ALLISON TRANS

CRUISE CONTROL MAX SET SPEED (MPH) 65 mph

CRUISE CONTROL MIN SET SPEED (MPH) 20 mph

CRUISE CONTROL AUTORESUME W/CLUTCH Omit

CRUISE'N BRAKE ENGAGEMENT DELAY (MPH) 0 mph

SMOOTH CRUISE Omit

ENGINE OVERSPEED COMPANY LIMIT (RPM) 2200 rpm

FUELED ENGINE OVERSPEED COMPANY LIMIT (RPM) 2100 rpm

VEHICLE OVERSPEED COMPANY LIMIT (MPH) 75 mph

FUELED VEHICLE OVERSPEED COMPANY LIMIT (MPH) 70 mph

IDLE LOGGING DELAY (MIN) 2

Monthly Trip Summary

PERIODIC TRIP HOUR OF DAY 0 (disable)

PERIODIC TRIP DAY OF WEEK 0 (disable)

PERIODIC TRIP DAY OF MONTH 1

DAYTIME RUNNING LIGHTS W/O OVERRIDE SWITCH

DRL OVERRIDE SWITCH SPEED THRESHOLD (MPH) 00

DRL OVERRIDE SWITCH OFF TIME (MIN) 00 mph

CO-PILOT FLEET TRIP PROGRAMMING ACCESS Fleet Level

FLEET MANAGEMENT VIA CO-PILOT Omit

EHT MAX ENGINE SET SPEED (RPM)

2100 rpm

EHT MIN ENGINE SET SPEED (RPM) 700 rpm

EHT VEHICLE SPEED RANGE LIMIT (MPH) 10 mph

EHT RAMP RATE (RPM/Sec)

EHT SINGLE SPEED CONTROL ACTIVATION Omit

EHT SINGLE SPEED CONTROL SET SPEED (RPM) 0000 rpm

EHT JUMP-TO-MIN SET SPEED Omit

EHT HOLD TO NEAREST RPM 00 rpm

EHT ACCEL-DECEL BUMP-UP RPM 00 rpm

EHT ACCEL-DECEL BUMP-DOWN RPM 00 rpm

ENGINE PROTECTION - OIL PRESSURE SHUTDOWN Furnish

ENGINE PROTECTION - COOLANT LEVEL SHUTDOWN Omit

ENGINE PROTECTION - COOLANT TEMP SHUTDOWN Furnish

ENGINE PROTECTION - ENGINE OIL TEMP SHUTDOWN Furnish

ENGINE PROTECTION TRANS OIL TEMP SHUTDOWN Furnish

FUEL ECONOMY INCENTIVE FOR USE WITH INSTRUMENT CLUSTER DISPLAY (C0J 0002)

FEI PENALTY TARGET FUEL ECONOMY No Driver Incentive

FEI PENALTY TARGET FUEL ECONOMY (MPG) 0.0

FEI PENALTY VEHICLE SPEED DECREASE (MPH) 0 mph

Liberty Rooming Senter

Description

FEI REWARD TARGET FUEL ECONOMY (MPG) 0.0

FEI REWARD VEHICLE SPEED INCREASE (MPH) 0 mph

FEI DISTANCE CALCULATION INTERVAL (Miles) 00

GOVERNOR SETTINGS FOR USE WITH MANUAL TRANSMISSIONS

GOVERNOR TYPE Min-Max Governor

REDUCED ENGINE RPM RANGE IN UPPER GEARS FEATURE Disable

Ref#: AIMQ026515A

ENGINE RPM LIMIT IN UPPER GEARS 0000

1st TRANS RATIO FOR REDUCED HIGH IDLE 0000

LAST TRANS RATIO FOR FULL HIGH IDLE 0000

ENGINE LOW IDLE SET SPEED (RPM) 700 rpm

DRIVER LOW IDLE ADJUST FEATURE ACTIVATION Omit

SMART IDLE FEATURE ACTIVATION Omit

SMART IDLE ELEVATED IDLE RPM TIME (MINS) 10

IDLE S/D ABS TAMPER CHECK Omit

IDLE COOLDOWN FEATURE ACTIVATION Omit

IDLE SHUTDOWN FEATURE ACTIVATION Furnish

IDLE SHUTDOWN TIME (MINS) 10

IDLE SHUTDOWN WARNING TIME (SECS) 30

IDLE SHUTDOWN WARM-UP TEMPERATURE (DEG F) 100

IDLE SHUTDOWN WARM-UP TIMER (MINS) 5

IDLE S/D OVERRIDE W/PTO Omit

IDLE S/D OVERRIDE W/EHT Omit

IDLE S/D OVERRIDE W/PTO Omit

IDLE S/D OVERRIDE W/ENGINE LOAD Omit

IDLE S/D OVERRIDE % ENGINE LOAD THRESHOLD 00

IDLE S/D CONTROL W/O Idle Shutdown

IDLE S/D OVERRIDE LOWER TEMP. THRESHOLD (DEG F) 00

IDLE S/D OVERRIDE UPPER TEMP. THRESHOLD (DEG F) 00

MAINTENANCE MONITOR FEATURE ACTIVATION Furnish

MAINTENANCE MONITOR OEM DEFAULT INTERVALS MP Vocational

MAINTENANCE DUE WARNING PERCENT 90

PTO 1 MAX ENGINE SET SPEED (RPM) 0000 rpm

PTO 1 MIN ENGINE SET SPEED (RPM) 700 rpm

PTO 1 VEHICLE SPEED RANGE LIMIT (MPH) 10 mph

PTO 1 RAMP RATE (RPM/Sec) 250

PTO 1 SINGLE SPEED CONTROL ACTIVATION Omit

PTO 1 SINGLE SPEED CONTROL SET SPEED (RPM) 0000 rpm

PTO 1 SINGLE SPEED CONTROL AUTOSET Omit

PTO 1 JUMP-TO-MIN SET SPEED Omit

PTO 1 VEHICLE LIMITING SPEED (MPH) 60 mph

PTO 1 HOLD TO NEAREST RPM 00 rpm

PTO 1 ACCEL-DECEL BUMP-UP RPM 00 rpm

PTO 1 ACCEL-DECEL BUMP-DOWN RPM 00 rpm

PTO 2 MAX ENGINE SET SPEED (RPM) 2100 rpm

PTO 2 MIN ENGINE SET SPEED (RPM) 0 rpm

PTO 2 VEHICLE SPEED RANGE LIMIT (MPH) 10 mph

Ref#: AIMQ026515A

Liberty Rooming Center

Description

PTO 2 RAMP RATE (RPM/Sec) 100

PTO 2 SINGLE SPEED CONTROL ACTIVATION Omit

PTO 2 SINGLE SPEED CONTROL SET SPEED (RPM) 0000 rpm

PTO 2 SINGLE SPEED CONTROL AUTOSET Omit

PTO 2 JUMP-TO-MIN SET SPEED Omit

PTO 2 VEHICLE LIMITING SPEED (MPH) 60 mph

PTO 2 HOLD TO NEAREST RPM 00 rpm

PTO 2 ACCEL-DECEL BUMP-UP RPM 00 rpm

PTO 2 ACCEL-DECEL BUMP-DOWN RPM 00 rpm

SPEED SENSOR TAMPER DETECTION SYSTEM ACTIVATION Furnish

SPEED SENSOR TAMPER DETECTION TORQUE LIMIT (%) 10

DEALER INFORMATION

ENGINE WARRANTY, 2YR/250,000 MILES ENGINE WARRANTY US10

PILOT INSPECTION, WITHOUT PILOT INSPECTION

PDI

PAC

AIR T TO CONNECT FILL HOSE

BODY AND MOUNTING KIT PER QUOTE JYLMQ2708

PERFORMANCE/GRAPHICS/TECH DATA

OVERWIDTH STATEMENT, OVERALL WIDTH EXCEEDS 96"

SOFT PRODUCTS/BULLDOG PROTECTION

W/O GUARDDOG CONNECT